

TOP CHW/CKW Series



TWO ROW COILS DIMENSIONS

Technical characteristics:

TIP/Type	B [mm]	H [mm]	C [mm]	L [mm]	N conn R
400/200-2R	400	200	510	180	3/4"
500/250-2R	500	250	620	180	3/4"
500/300-2R	500	300	620	180	3/4"
600/300-2R	600	300	720	180	1"
600/350-2R	600	350	720	180	1"
700/400-2R	700	400	830	180	1"
800/500-2R	800	500	940	180	5/4"
1000/500-2R	1000	500	1140	180	5/4"
400/400-2R	400	400	520	180	3/4"
500/500-2R	500	500	630	180	1"
600/600-2R	600	600	740	180	5/4"
800/600-2R	800	600	940	180	5/4"
800/800-2R	800	800	940	180	6/4"
1000/800-2R	1000	800	1160	200	6/4"
1200/800-2R	1200	800	1390	200	2"
1000/1000-2R	1000	1000	1190	200	2"
1200/1000-2R	1200	1000	1390	200	2"
1300/1300-2R	1300	1300	1510	200	2"
1400/1400-2R	1400	1400	1610	200	2 1/2"
1600/1200-2R	1600	1200	1810	200	2 1/2"
1600/1600-2R	1600	1600	1810	200	3"
2000/1600-2R	2000	1600	2210	200	3"

FOUR ROW COILS DIMENSIONS

Technical characteristics:

TIP/Type	B [mm]	H [mm]	C [mm]	L [mm]	N conn R
400/200-4R	400	200	510	200	3/4"
500/250-4R	500	250	620	200	1"
500/300-4R	500	300	620	200	1"
600/300-4R	600	300	720	200	1"
600/350-4R	600	350	720	200	1"
700/400-4R	700	400	830	200	5/4"
800/500-4R	800	500	940	200	6/4"
1000/500-4R	1000	500	1140	200	6/4"
400/400-4R	400	400	520	200	1"
500/500-4R	500	500	630	200	5/4"
600/600-4R	600	600	740	200	6/4"
800/600-4R	800	600	940	200	2"
800/800-4R	800	800	940	200	2"
1000/800-4R	1000	800	1160	220	2"
1200/800-4R	1200	800	1390	220	2 1/2"
1000/1000-4R	1000	1000	1190	220	2 1/2"
1200/1000-4R	1200	1000	1390	220	3"
1300/1300-4R	1300	1300	1510	220	3"
1400/1400-4R	1400	1400	1610	220	3"
1600/1200-4R	1600	1200	1810	220	3"
1600/1600-4R	1600	1600	1810	220	4"
2000/1600-4R	2000	1600	2210	220	4"